

### TO MAKE A WOOD/BOARD EFFECT

## KABE DP2

Anti-adhesive product  
for silicone moulds



### MAIN ADVANTAGES

- Reduce adhesion of the mortar to the silicone mould
- Facilitates obtaining a clear wood structure
- Easy to apply
- Safe to use

### AREAS OF APPLICATIONS

Anti-adhesive product used to make the wood/board effect (WOOD DECOR) by using a silicone mould. The product is used on a silicone mould to prevent it from sticking with **KOMBI DECOR PRINT** mineral decorative mortar while impressing the wood/board structure. The product is intended for use by trained contractors.

### TECHNICAL SPECIFICATION

**Base:** isobutyric acid monoester;

**Density:** ca. 0.95 kg / dm<sup>3</sup>;

**Temperature of application:** from +5°C to +25°C.

**Approximate consumption:** ca. 0.1 l/m<sup>2</sup> of wood/board effect;

**Packaging:** Single-use plastic packaging of 5 l of the product.

**Storage:** The product should be stored in a cool, dry, well-ventilated room. Avoid direct sunlight, heat sources and strong oxidizing agents. Keep out of the reach of children. If necessary, seek medical advice, show the container or label.

**Shelf life:** up to 24 months from the date of production.

### APPLICATION METHOD

Apply the anti-adhesive agent evenly on the silicone mould using a brush, without forming puddles. During modelling the wood structure, control the quality of the impressed texture and repeat periodically the application of the anti-adhesive agent on the silicone mould. Applying too small amount of the product on silicone mould may cause mortar sticking to mould, in result is a worse quality of the impressed texture. **Note:** Work should be carried out at a temperature of + 5 °C to + 25 °C. The rooms should be ventilated during works (if necessary, use dust collector). Do not pour leftovers into the sewage system. Avoid inhaling the vapors. Avoid contact with eyes and skin. Do not eat or smoke during the working process with the mixture. After finishing work with the product wash your hands. In case of skin contact, wash dirt with soap and water. In case of contact with the eyes, they should be rinsed with water for 10-15 min and seek medical advice, showing the label or safety data sheet.

The information contained in the technical sheet, in particular, recommendations regarding the method and conditions of application and the scope of application and use of our products, have been developed based on our professional experience. This technical data sheet specifies the scope of use of the material and the recommended method of carrying out works, but it cannot replace the professional preparation of the performer. The manufacturer guarantees the quality of the product, while it does not affect the conditions and the method of its use. Considering that conditions in which products are used may change, in case of doubt it is recommended to carry out own tests. We are not responsible for the above information or any verbal recommendation related to it, except cases of gross negligence or deliberate fault. This technical data sheet replaces all previous versions applicable to this product.