

## FOR WOOD IMITATION EFFECTS

## KABE DP2

Anti-adhesive product  
for silicone moulds



## MAIN ADVANTAGES

- Reduces adhesion of mortar to the silicone mould
- Facilitates obtaining a clear wood structure
- Easy to apply
- Safe to apply

## AREAS OF APPLICATION

The product is designed for making the wood/board effect (WOOD DECOR) by using a silicone mould. It is used on a silicone mould to prevent it from sticking to **KOMBI DECOR PRINT** mineral decorative mortar while impressing the wood/board structure. The product is intended for use by trained workers.

## TECHNICAL DATA

**Base:** isobutyric acid monoester;

**Density:** approx. 0.95 kg/dm<sup>3</sup>;

**Temperature of application:** from +5°C to +25°C;

**Approximate consumption:** approx. 0.1 l/m<sup>2</sup> of wood/board effect;

**Packaging:** Disposable plastic packaging containing 5 litres of product;

**Storage:** The product should be stored in a cool, dry, well-ventilated room. Avoid direct sunlight, heat sources and strong oxidising agents. Keep out of the reach of children. If necessary, seek medical advice and show the container or label.

**Shelf life:** up to 24 months from the date of production.

## HOW TO USE

Apply the anti-adhesive agent evenly on the silicone mould using a brush, without forming puddles. During modelling the wood structure, control the quality of the impressed texture and repeat periodically the application of the anti-adhesive agent on the silicone mould. Applying too small amount of the product on silicone mould may cause mortar sticking to mould, resulting in lower quality of the impressed texture. **NOTE!** Work should be carried out at a temperature of +5°C to +25°C. The rooms should be well ventilated during works (if necessary, use a dust collector). Do not pour leftovers into the sewage system. Avoid inhaling the vapours. Avoid contact with eyes and skin. Do not eat or smoke while working with the mixture. After finishing work with the product wash your hands. In case of skin contact, wash dirt with soap and water. In case of contact with the eyes, rinse them with water for 10-15 minutes and seek medical advice, showing the label or safety data sheet.

The information contained in the technical sheet, in particular the recommendations regarding the method and conditions of application, as well as the scope of application and use of our products, have been developed based on our professional experience. This technical data sheet specifies the scope of use of the material and the recommended method of carrying out works, but it cannot replace the professional knowledge of the worker. The manufacturer guarantees the quality of the product, whereas they have no control over the conditions and the method of its use. Considering that conditions, in which products are used, may change, in case of doubt, it is recommended to carry out own site tests. We are not liable for the above-mentioned information or any verbal recommendation related thereto, except in cases of gross negligence or wilful misconduct. This technical data sheet replaces all previous versions applicable to this product.